

Ceiling Flat – Data Sheet

Description:

Paint Tech **Ceiling Flat** has been formulated for use on ceilings in dining rooms, bedrooms and lounges. It dries to a architectural flat finish with excellent coverage and hiding power. This product has very low odour and low splatter when applying.

Physical Properties

r ilysical r ioperties	
Resin Type:	Modified Acrylic
Solvent:	Water
Colour:	White and tinted pastel shades
Finish:	Matt
Drying time:	60 minutes @ 20°C
Recoat time:	2 hours
Dry Film Thickness:	35µ minimum recommended per coat
No. of coats:	1-2
Theoretical Coverage	10m₂ per litre to attain 35µ
Primer Needed:	Yes
Thinning & Cleaning:	Water

Performance:

- Easy application with minimal roller splatter
- Low odour
- 1 coat may be sufficient with careful application
- Can be applied over gypsum plasterboard, fibrous plaster and for repaints

Limitations:

- Do not apply when temperature is below or expected to fall under 10°C.
- Not recommended in bathrooms, laundries kitchens and other areas of high humidity.
- Will not adhere to powdery substrates and non penetrating surfaces such as gloss and semi-gloss paint unless they are well sanded.

Substrate Preparation:

Ensure all surfaces are clean, dry and dust free. Previously painted surfaces should be sanded.

- Apply 1 full coat of Paint Tech **Wall Board Sealer** to new plasterboard and fibrous plaster. Allow to dry, sand to required level of finish and apply **Ceiling Flat.**
- For old and yellowed plasterboard and painted surfaces use Paint Tech All-Prime or Paint Tech Alkyd Pigmented Sealer as the first coat.

Application:

Ceiling Flat may be applied by brush, roller or spray. Do not thin more than 10% as necessary for application method. Clean up with water.

Although the information and recommendations set down here in this document are presented in good faith and believed to be correct, Paint Tech makes no representation as to the completeness and accuracy thereof. In no event will Paint Tech be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Data Sheet refers